

DECLARATION OF PERFORMANCE

DOP PA-Hain 325

in accordance with (EU) No. 305/2011 (CPR) of the European Parliament and the Council of 9th March 2011

1. Unique identification code of the product-type:
DOP PA-Hain 325
Castello | naturally oiled, Ambiente| naturally oiled, Viale | naturally oiled, Primus | naturally oiled,
FINO 90 | naturally oiled, FINO 55 | naturally oiled
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
Multi-layer parquet according to EN 13489 for floating installation or full-surface bonding in buildings
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
Hain Naturböden GmbH & Co. KG, Zum Walde 18, D-59602 Rütthen
5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3
- 6 a). In case of the declaration of performance concerning a construction product covered by a harmonised standard:
Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).
NB 0766 - EPH - Entwicklungs- und Prüflabor Holztechnologie GmbH, Zellescher Weg 24, D-01217 Dresden NB 2097 - eco-INITIUT Germany GmbH, Schanzenstrasse 6-20, Carlswerk Kupferzug 5.2, D-51063 Köln
NB 1658 - TFI Aachen GmbH, Charlottenburger Allee 41, D-52068 Aachen NB 0432 - Materialprüfungsamt Nordrhein-Westfalen (MPA NRW) Außenstelle Erwitte, Auf den Thränen 2, D-59597 Erwitte
.....
Notified Body

6 b). In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
not applicable

Essential characteristics	Performance			Harmonised technical specification
Thickness	12 mm	15 mm	17 mm	
Reaction to fire	 D _{fl} -s1 when completely glued with the adhesive Hain-Schubfest	 D _{fl} -s1 in connection with a minimum mean density of ≥ 500 kg/m ³ and a minimum total thickness of 15 mm  C _{fl} -s1 when completely glued with the adhesive Hain-Elastic	 D _{fl} -s1 in connection with a minimum mean density of ≥ 500 kg/m ³ and a minimum total thickness of 17 mm	EN 14342:2013
Emission (release) of formaldehyde		E1		EN 14342:2013
Emission of (content) of pentachlorophenol		≤ 5 × 10 ⁻⁶ⁿ		EN 14342:2013
Breaking strength				EN 14342:2013
Slip resistance				EN 14342:2013
Thermal conductivity				EN 14342:2013
	0,112 W/(m*K)	0,106 W/(m*K)	0,106 W/(m*K)	
Durability without treatment with wood preservative (i.e. natural durability)	Class 1			EN 14342:2013

8. The performance of the above product corresponds to the declared performance(s)
The manufacturer named above is solely responsible for preparing the declaration of performance in accordance with Regulation (EU) No. 305/2011
Signed for and on behalf of the manufacturer by:

.....
Rudolf Hester, Head of Quality Management
(name and function)

.....
D-59602 Ruethen-Meiste, 04.04.2025
(place and date of issue)



 (signature)